



Model LP-CP308D



IP54 / IK10

Type 2 Socket

7" LCD Screen

ISO5118-2

OCPP1.6 J/OCPP2.0.1 Upgradeable

RFID (ISO/IEC14443 A/B)

3-layer housing for easy maintenance

LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional



Model Name	LP-CP308D
Power Specification	
Input AC Rating	400Vac±10%
Input Max.AC Current	32A * 2
Frequency	50/60Hz
Max.Output Power	22kW * 2
User Interface & Control	
Display	7" LCD Screen
LED Indicator	Yes
User Authentication	RFID (ISO/IEC14443 A/B), APP
Communicartion	
Network Interface	LAN, Wi-Fi and Bluetooth Standard, 3G/4G Optional
Communication Protocol	OCPP1.6 J/OCPP2.0.1 Upgradeable
Environmental	
Operation Temperature	-30℃~50℃
Humidity	5%~95% RH, Non-condensing
Altitude	≤ 2000m, No Derating
Mechanical	
IP/IK Level	IP54 / IK10
Charging Pile Dimensions (W×D×H)	400mm×200mm×1370mm
Base Dimensions (W×D×H)	450mm×290mm×40mm
Weight	40kgs
Protection	
Multiple Protection	OVP(Over Voltage Protection), OCP(Over Current Protection), OTP(Over Temperature Protection), UVP(Under Voltage Protection), SPD(Surge Protection Detection), Grounding Protection, SCP(Short Circuit Protection), Control Pilot Fault, Relay Welding Detection, RCD(DC 6mA)
Regulation	
Safety	IEC 61851-1, IEC 61851-21-2
Certificate is in processing	CE, CB, UKCA
Charging Interface	IEC 62196-2 Complaint,Type 2 Socket